

## Hot Stamping Foil – MEG Grade

### Product Data Sheet

#### Foil Specifications

---

<b>Polyester Film Thickness:</b>	12µm (0.012mm)
<b>Standard Width:</b>	25" (64cm)
<b>Standard Length(s):</b>	200' (61m); 400' (122m); 1000' (305m); 2000' (610m); 3000' (914m); 4000' (1219m)
<b>Custom Widths and Lengths:</b>	Available upon request

#### Stamping Effects

---

<b>Release:</b>	Very easy
<b>Detail:</b>	Heavy
<b>Appearance:</b>	Metallic
<b>Overstamp with Foil:</b>	NA
<b>Overprint with Inks and Varnishes:</b>	NA

#### Product Performance

---

<b>Abrasion Resistance:</b>	Good abrasion and scratch resistance
<b>Adhesion Characteristics:</b>	Most uncoated graphic arts papers Excellent for edge gilding
<b>Running Temperature:</b>	230–280°F / 110–138°C

#### Storage and Shelf Life Requirements

---

Two (2) years in dry, climate-controlled conditions  
and stored on its end, not on side

#### Industries Served

---

Bibles, Books, Stationery, Business Cards, Planners

#### Product Application

---

Edge gilding, Foil Decorating